



Download provided by eLABZ.com
the information source for CNC,
Robotics, Microcontroller and other
electronics projects

<http://elabz.com/>

HL45023TG - 445nm / 80mW -

GaN Blue High Power Laser Diode


Target
Rev.0
5. Nov. 2010

■ Applications


- Pico projector
- Various light source

■ Internal circuit

•HL45023TG



■ Outline



■ Features

- Optical output powr: $P_o=55\text{mW(CW)}$
- Blue lasing : $\lambda_p=445\text{nm}$
- Low operating current: $I_{op}=90\text{mA Typ.}$
- Low operating voltage: $V_{op}=5.0\text{V Typ.}$
- Small package: $\phi 3.8\text{mm}$
- Single transverse mode oscillation

■ Absolute Maximum Ratings($T_c=25^\circ\text{C}$)

Item	Symbol	Ratings	Unit
Optical output power	P_o	80	mW
LD Reverse Voltage	$V_{R(LD)}$	2	V
Operating Temperature	T_{opr}	-10 ~ +70	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40 ~ +85	$^\circ\text{C}$

■ Optical and Electrical Characteristics($T_c=25^\circ\text{C}$)

Item	Symbol	Min.	Typ.	Max.	Unit	Test condition
Threshold current	I_{th}	-	30	50	mA	-
Operating current	I_{op}	-	90	130	mA	$P_o=55\text{mW}$
Operating voltage	V_{op}	-	5.0	6.0	V	$P_o=55\text{mW}$
Lasing Wavelength	λ_p	440	445	460	nm	$P_o=55\text{mW}$
Beam divergence Parallel to the junction	$\theta_{//}$	5	8.5	13	$^\circ$	$P_o=55\text{mW}$
Beam divergence Perpendicular to the junction	θ_{\perp}	13	18	23	$^\circ$	$P_o=55\text{mW}$

Note : This type is underdevelopment. Therefore, this data sheet may be changed without any notice.

Cautions

1. Opnext Japan, Inc. (OPJ) neither warrants nor grants licenses of any our rights or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. OPJ bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. OPJ makes every attempt to ensure that its products are of high quality and reliability. However, contact our sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by OPJ particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. OPJ bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating OPJ product does not cause bodily injury, fire or other consequential damage due to operation of the OPJ product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from OPJ.
7. Contact our sales office for any questions regarding this document or OPJ products.

1. The laser light is harmful to human body especially to eye no matter what directly or indirectly. The laser beam shall be observed or adjusted through infrared camera or equivalent.
2. This product (without violet laser diode) contains gallium arsenide (GaAs), which may seriously endanger your health even at very low doses. Please avoid treatment which may create GaAs powder or gas, such as disassembly or performing chemical experiments, when you handle the product. When disposing of the product, please follow the laws of your country and separate it from other waste such as industrial waste and household garbage.
3. Definition of items shown in this CAS is in accordance with that shown in Opto Device Databook issued by OPJ unless otherwise specified.

Sales Offices



Opnext Japan, Inc.

Takagi Bldg., 3F, 1-3-9, Iwamoto-cho, Chiyoda-ku, Tokyo 101-0032, Japan
Tel: (03) 3865-5591

For the detail of Opnext, Inc., see the following homepage:

Japan (Japanese) <http://www.opnext.com/jp/products/>

Other area (English) <http://www.opnext.com/products/>

© 2010 Opnext Japan, Inc., All rights reserved. Printed in Japan